



**TL-Buchsen**

Typ Standardbohrung Toleranz G7 mit Nut JS9 nach DIN 6885

1008	10	11	12	14	15	16	18	19	20	22	24								
1108	10	11	12	14	15	16	18	19	20	22	24	25							
1210	11	12	14	15	16	18	19	20	22	24	25	28	30						
1215	14	16	18	19	20	22	24	25	28	30									
1310	14	16	18	19	20	22	24	25	28	30	32								
1610	12	14	15	16	18	19	20	22	24	25	28	30	32	35	38	40			
1615	14	16	18	19	20	22	24	25	28	30	32	35	38	40					
2012	16	18	19	20	22	24	25	28	30	32	35	38	40	42	45	48	50		
2517	19	20	22	24	25	28	30	32	35	38	40	42	45	48	50	55	60	65	
3020	25	28	30	32	35	38	40	42	45	48	50	55	60	65	70	75			
3030	35	38	40	42	45	48	50	55	60	65	70	75							
3525	35	38	40	42	45	48	50	55	60	65	70	75	80	85	90	95	100		
3535	35	38	40	42	45	48	50	55	60	65	70	75	80	85	90				
4030	40	42	45	48	50	55	60	65	70	75	80	85	90	95	100	105	110	115	
4040	40	42	45	48	50	55	60	65	70	75	80	85	90	95	100				
4535	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125				
4545	55	60	65	70	75	80	85	90	95	100	105	110							
5040	70	75	80	85	90	95	100	105	110	115	120	125							
5050	70	75	80	85	90	95	100	105	110	115	120	125							
6050	95	100	105	110	115	120	125	130	135	140	145	150							